

Distribution Enclosure



- High thermal stability - ASA plastic
- Transparent door
- UV Stable
- Current rating 63A
- IP65 rating – Inside / Outside use
- Earth & neutral bars included
- Suitable for Photovoltaic applications
- Key accessory

Options & Ordering

E — **04** **W**

| | |
|-----------------|-----------|
| Modules / Poles | 04 |
| Modules / Poles | 08 |
| Modules / Poles | 12 |
| Modules / Poles | 36 |



Technical Data

| | |
|-------------------|----------------|
| Protection class | IP65 |
| Isolation class | II |
| Impact kit | IK07 |
| Normal voltage | 400V AC |
| Temperature range | -25°C to +60°C |
| Colour | RAL 7035 |
| IEC capability | 60670-24 |

| Type | Description | Number of Terminals PE/N | Dimensions H x W xD | Entries Description |
|-------|---------------------|--------------------------|---------------------|---|
| E-04W | 4 Module Enclosure | 4/4 | 200 x 127 x 120 | 4 x M20 + 4x M25/M32 |
| E-08W | 8 Module Enclosure | 8/8 | 200 x 200 x 120 | 8 x M20 + 6x M25/M32 |
| E-12W | 12 Module Enclosure | 10/10 | 258 x 318 x 142 | 12 x M20 + 10x M25/M32 + 4x M32/M40 + 2x Knockout plate 37x90mm |
| E-24W | 24 Module Enclosure | 13/13 | 383 x 318 x 142 | 12 x M20 + 10x M25/M32 + 4x M32/M40 + 4x Knockout plate 37x90mm |
| E-36W | 36 Module Enclosure | 15/15 | 507 x 318 x 142 | 12 x M20 + 10x M25/M32 + 4x M32/M40 + 6x Knockout plate 37x90mm |

Each enclosure comes with a set of accessories:

- 6 way divisible blanking plates
- 4x Wall plug and screws
- 4x internal screw caps
- Application identifier stickers