


Data Sheet

Type Number 399
Designation IEC SR 57
System Silver oxide / Zinc /
 KOH - Electrolyte



Nominal Voltage 1,55 V
Typical Capacity C 42 mAh
 Load 13 kOhm, at 20°C down to 1.3 V

Weight (approx.) 0,75 g
Volume 0,17 ccm
Coding..... Manufacturing Month/Year by
 Letter Code

Temperature Ranges min max.
 Storage -10°C 65 °C
 Discharge -10°C 65°C

Dimensions min max.
 Diameter 9,15 9,5
 Height (A/B) 2,4 2,7

Segment Watch / High Drain

Main Applications Watch
 Photo
 Electronic

Typical Capacities (at 20°C)

| Discharge Type | Load | End Voltage: | 1.3 V |
|----------------|---------|-----------------|-------|
| Continuous | 13000 Ω | Time: | 350 h |
| 24h/d,7d/w | | Capacity [mAh]: | 42 |
| Current [μA]: | 120 | Energy [MWh]: | 65 |

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
 Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!
 Date of issue: 07.08.2003