



BUZZERS POUR SIGNALISATIONS INDUSTRIELLES

V 12-24-48-110-230-240 (±10%)		==		~ 50/60 Hz		On ∞	
AUTO-EXTINGUIBLE	IP 30					°C -30 +50	




BIP 81
BIP 81

11 24




BIP 81 MCA

V ==	12	24	48	110	230	240
V ~				110	230	240
mA	3.5	3.5	3.5	3.5	3.5	3.5
dB(A)1m	72	72	72	72	72	72
Hz 1800						



Kg. 0,04



Kg. 0,07

- Installation à encastrer dans des perçages carrés

BIP8112DA	42300	BIP81230D	42305	BIP81MCA12DA	42309	BIP81MCA230D	42314
BIP8124DA	42301	BIP81230A	42306	BIP81MCA24DA	42310	BIP81MCA230A	42315
BIP8148DA	42302	BIP81240D	42307	BIP81MCA48DA	42311	BIP81MCA240D	42316
BIP81110D	42303	BIP81240A	42308	BIP81MCA110D	42312	BIP81MCA240A	42317
BIP81110A	42304			BIP81MCA110A	42313		




BIP 92
BIP 92

11 24 36




BIP 92 MCA

V ==	12	24	48	110	230	240
V ~				110	230	240
mA	5	5	5	5	5	5
dB(A)1m	75	75	75	75	75	75
Hz 3600						



Kg. 0,04




Kg. 0,07

- Installation à encastrer dans des perçages ronds (Ø 16-22-30 mm)

BIP9212DA	42318	BIP92230D	42323	BIP92MCA12DA	42327	BIP92MCA230D	42332
BIP9224DA	42319	BIP92230A	42324	BIP92MCA24DA	42328	BIP92MCA230A	42333
BIP9248DA	42320	BIP92240D	42325	BIP92MCA48DA	42329	BIP92MCA240D	42334
BIP92110D	42321	BIP92240A	42326	BIP92MCA110D	42330	BIP92MCA240A	42335
BIP92110A	42322			BIP92MCA110A	42331		



ADAPTATEUR BIP
ADA BIP



Kg. 0,05

- Adaptateurs DIN pour montage sur faces avant disponibles aussi montés et câblés

ADABIP 33500




11 24 36

BIP OS 93
BIP OS 93




11 24

V ==	12	24	48	110	230	240
V ~				110	230	240
mA	5	5	5	5	5	5
dB(A)1m	75	75	75	75	75	75
Hz 4000						



Kg. 0,04



Kg. 0,06

- Installation à encastrer dans des perçages ronds (Ø 22 mm) ou sur un support orientable


BIPOS9312DA	42336	BIPOS93230D	42341
BIPOS9324DA	42337	BIPOS93230A	42342
BIPOS9348DA	42338	BIPOS93240D	42343
BIPOS93110D	42339	BIPOS93240A	42344
BIPOS93110A	42340		



BIP 84
BIP 84

11 24 37

V ==	12	24	48	110	230	240
V ~				110	230	240
mA	6	6	6	6	6	6
dB(A)1m	80	80	80	80	80	80
Hz 2200÷3500						



Kg. 0,08

- Installation à encastrer dans des perçages ronds (Ø 30 mm) - double LED

BIP8412DA	42345	BIP84230D	42350
BIP8424DA	42346	BIP84230A	42351
BIP8448DA	42347	BIP84240D	42352
BIP84110D	42348	BIP84240A	42353
BIP84110A	42349		