

WFE 2ES - Volume Extraction Unit

BestellNr.:0053650699



The integrated economy-filter (HEPA filter H12) is easy to replace. 2 workplaces are connectable. Kit will be delivered with one extraction arm.

For applications where volume extraction is more suitable, e.g. solder baths, hot air soldering, micro solders and gluing work, Weller offers the mobile systems WFE 2S and WFE 4S. The units purify the air at upto 8 workplaces. A wide range of accessory is available for each system.

Top Attributes

- Voltage: 230 V / 50 Hz (115 V / 60 Hz)
- Dimensions in mm: 320 x 320 x 395 (L x W x H)
- Electrical Power: 115 VA
- Noise level: 55 db (A) at 1 m distance
- Max. pressure: 1800 Pa
- Max. airflow: 220 m³/h
- Max. capacity: 2 work places
- Filter: Fine dust filter F5, HEPA filter H12 (99.5% against particle ca. 0.3 µm) combined with wide gas filter (active carbonate foam)

Technical Data

Computer interface for remote control	RS 232
Color	Weller Blue
Operation mode / speed	Free, Potentiometer
Filter type	Compact filter (HEPA filter H13 + wide band gas filter 50% active carbon / 50% Puratex) and Fine dust filter F 5
Portable	No
Electronic filter control	No
Max. delivery / extraction rate (m³/h)	230.0

Packaging information

Shelf pack size (Units per shelf pack)

Single