

Electrical Characteristics

Nominal Impedance: 50 ohms
 Frequency Range: DC to 4 GHz
 VSWR: 1.35:1 maximum
 Insertion Loss: 0.2 dB at 3 GHz
 Operating Voltage (rms): 500 V maximum at sea level
 Dielectric Withstand Voltage (rms): 1500 V maximum at sea level
 Contact Resistance: 1.5 milliohms maximum
 Insulation Resistance: 5000 megohms minimum


Mechanical Characteristics

Mating Cycles: 500 cycles minimum
 Interface Dimensions: Conform to MIL-C-39012


Environmental Characteristics

Temperature Range: -65 °C to +165 °C

PART	DESCRIPTION
1	Body Brass, nickel plated 1.78µm
2	Ferrule Brass, nickel plated 1.78µm
3	Contact Brass, gold plated 0.076µm - 0.127µm
4	Dielectric PTFE
5	Nut Brass, nickel plated 1.78µm
6	Washer Steel, nickel plated 1.78µm
7	Gasket Silicone, red



For stripping and assembly instructions see Drawing Number: VAIB4101



EMERSON
Network Power

Connectivity Solutions
 7-13 Russel Way,
 Widford Industrial Estate,
 Chelmsford, Essex,
 CM1 3AA, UK.
 Tel: +44 (0) 1245 359515
 Fax: +44 (0) 1245 358938

SCALE: Not To Scale

DIMENSIONS: mm

TOLERANCES:
 ± 0.2mm unless
 otherwise stated

DRAWN BY: S Nash

CHECKED BY: R Drenan

APPROVED BY: P D Couzens

DATE: 27 Jun 02

TITLE:

BNC Bulkhead Crimp Jack
for RG58

PART NUMBER:

VB40-2051

PAGE: 1 of 1

DESCRIPTION OF REVISION	APPVD	ISS	DATE
Dim change	MS	5	7 Jan 08
Altered Address	KA	4	14 Aug 07
HEX Modification	SN	3	27 Jun 02
CAD Issue	SN	2	21 Jan 02
First Issue	YL	1	15 May 96