

Product Detail Page



TFT-1904LED

Number: 18.3100

LCD colour monitor in a metal housing for surveillance systems, with LED backlight for a very detailed image of high colour brilliance, with HDMI™ connection.

- Visible diagonal screen size: 48cm (19")
- Response time: 3.7ms
- Angle of view: horizontal 170°, vertical 160°
- Contrast ratio: 1,000:1
- Brightness: 250cd/m², 16.7 million colours
- 2 video inputs, switchable, with feed-through output
- 2 RCA audio inputs, with feed-through output
- Additional connections: HDMI™, DVI, VGA and S-video
- Built-in speaker
- Operation via on-screen menu (OSD)
- Display options: full image, picture-in-picture (PIP), picture-over-picture (POP)
- Perforated rear panel according to VESA 100 standard
- Supplied with base, VGA cable, RCA audio cable and matching PSU

Technical Facts

General information

Colour system	PAL/NTSC
Resolution	1,280x1,024 pixels
Inputs	
Audio	
Video	1V _{pp} /75Ω
Outputs	
Audio	-
Video	1V _{pp} /75Ω
Power supply	12V = /5A via suppl. PSU
Admiss. ambient temp.	0-40 °C
Dimensions	425x352x53mm (w/o base)
Mount. cutout/mount. depth	-
Dimensions front panel	-
Weight	3.7kg (w/o base)
Connections	
Audio/video	2 x BNC in (video 1+2) 2 x BNC out (video 1+2), feed-through output 1 x D-SUB (VGA) 1 x DVI 1 x HDMI™ 1 x S-video 1 x 3.5mm stereo jack, audio in 2 x RCA, audio out 2 x RCA, audio out, feed-through output 1 x USB



Power supply

1 x low-voltage jack

