

**Telemecanique Sensors**

1875 Founders Drive

Dayton, OH 45420-4017

Toll Free: (800) 435-2121 • Phone: (937) 252-2121 • Fax: (937) 258-5830

E-Mail: [hydepark@us.schneider-electric.com](mailto:hydepark@us.schneider-electric.com) • Web site: [www.sesensors.com](http://www.sesensors.com)**Item # XX7V1A1PAM12, Ultrasonic Sensor, Discrete, 18 mm snout Dual Mount, 12-24 VDC**

List Price QUOTE

**Ultrasonic Sensor, Discrete, 18 mm snout Dual Mount, 12-24 VDC**

Ø18 mm mountable or flat profile mountable sensors for various mounting needs

- Discrete proximity, analog or dual-level sensing
- UL, CE, RoHS

**SPECIFICATIONS**

Length	59.69 mm 2.35 in
Width	18.0 mm 0.71 in
Depth	43.7 mm 1.72 in
Face Material	Glass Epoxy
Body Style	Dual Mount
Volts Type	DC
Voltage Range	12-24 VDC
Current Consumption	40 mA
Circuit Type	Normally Open
Output Mode	PNP
Temp Range	-30° to 70° C (-22° to 158° F)
Max Load	100 mA
Sensing Range	50.8 to 508 mm (2.0 to 20.0 in)
Response Time	15 ms
Sonic Frequency	300 kHz

Field Configurable	No
DeviceNet	No
NEMA Type	4X (indoor use only)
Connector Type	M12
Standards	UL, CE Rohs
Special Features	Tamper Proof with PB100 Pushbutton Accessory
IP Rating	IP67