

CODE STOCK PART NUMBER	RÉFÉRENCE	LAMPE			BALLAST					
		TYPE	CULOT SOCKET	WATTS	DIMENSIONS L x l x H (MM)	ENTRAXE/FIXING CENTERS (MM)	POIDS WEIGHT (KG)	COURANT (230V 50 Hz) A	T <sub>c</sub> °C	T <sub>A</sub> °C
<b>LONGUEUR 359 MM : 2 LAMPES PAR BALLAST/2 lamps for ballast</b>										
127196	<b>MLS 239 S</b>	TC-F	2G10	2 x 18	359 x 30 x 28	350	0,300	0,16	75	- 25 + 60
		TC-F	2G10	2 x 24	359 x 30 x 28	350	0,300	0,23	75	- 25 + 60
		TC-F	2G10	2 x 36	359 x 30 x 28	350	0,300	0,32	75	- 25 + 60
		TC-L	2G11	2 x 18	359 x 30 x 28	350	0,300	0,16	75	- 25 + 60
		TC-L	2G11	2 x 24	359 x 30 x 28	350	0,300	0,23	75	- 25 + 60
		TC-L	2G11	2 x 36	359 x 30 x 28	350	0,300	0,32	75	- 25 + 60
<b>LONGUEUR 103 MM : 1 LAMPE PAR BALLAST/1 lamp for ballast</b>										
127198	<b>MQTM 2642 S</b>	TC-DE	G24Q3	26	103 x 67 x 31	110	0,160	0,12	70	- 20 + 50
		TC-TE	GX24Q3	26	103 x 67 x 31	110	0,160	0,12	70	- 20 + 50
		TC-TE	GX24Q3	32	103 x 67 x 31	110	0,160	0,15	70	- 20 + 50
		TC-TE	GX24Q4	42	103 x 67 x 31	110	0,160	0,20	70	- 20 + 50
		TC-L	2G11	18	103 x 67 x 31	110	0,160	0,09	70	- 20 + 50
		TC-L	2G11	24	103 x 67 x 31	110	0,160	0,12	70	- 20 + 50
		TC-L	2G11	36	103 x 67 x 31	110	0,160	0,15	70	- 20 + 50
		TC-L	2G11	40	103 x 67 x 31	110	0,160	0,19	70	- 20 + 50
		TC-F	2G10	18	103 x 67 x 31	110	0,160	0,09	70	- 20 + 50
		TC-F	2G10	24	103 x 67 x 31	110	0,160	0,12	70	- 20 + 50
		TC-F	2G10	36	103 x 67 x 31	110	0,160	0,15	70	- 20 + 50
<b>LONGUEUR 123 MM : 2 LAMPES PAR BALLAST/2 lamps for ballast</b>										
127197	<b>MLS 236 Q</b>	TC-E	2G7	2 x 5	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-E	2G7	2 x 7	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-E	2G7	2 x 9	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-E	2G7	2 x 11	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-DE	G24Q1	2 x 10	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-DE	G24Q1	2 x 13	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-DE	G24Q2	2 x 18	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-DE	G24Q3	2 x 26	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-TE	GX24Q1	2 x 13	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-TE	GX24Q2	2 x 18	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-TE	GX24Q3	2 x 26	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		TC-TE	GX24Q3	2 x 32	123 x 79 x 33	129,5	0,190		75	- 25 + 60
		127199	<b>MQTM 2632 D</b>	TC-DE	G24Q3	2 x 26	123 x 79 x 33	129,5	0,240	0,23
TC-TE	GX24Q3			2 x 26	123 x 79 x 33	129,5	0,240	0,23	70	- 20 + 50
TC-TE	GX24Q3			2 x 32	123 x 79 x 33	129,5	0,240	0,30	70	- 20 + 50
TC-L	2G11			2 x 18	123 x 79 x 33	129,5	0,240	0,16	70	- 20 + 50
TC-L	2G11			2 x 24	123 x 79 x 33	129,5	0,240	0,23	70	- 20 + 50
TC-L	2G11			2 x 36	123 x 79 x 33	129,5	0,240	0,30	70	- 20 + 50
TC-F	2G10			2 x 18	123 x 79 x 33	129,5	0,240	0,16	70	- 20 + 50
TC-F	2G10			2 x 24	123 x 79 x 33	129,5	0,240	0,23	70	- 20 + 50
TC-F	2G10			2 x 36	123 x 79 x 33	129,5	0,240	0,30	70	- 20 + 50

