



Version with antirotation pegs is available on 2 poles connections.
Disponibile per connessioni a 2 poli versioni con perni antitorsione.

GENERAL INFORMATIONS

pitch:	5,08 mm
housing height:	10,60 mm
housing depth:	8.1 mm
dimensional class:	slow
wire section:	1.5 mm ² / 16 AWG
clamp opening size:	2.6 × 2 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	13.5A
voltage:	250V
impulse voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
recommended torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



EN 60998-1



-



UL 1059

13.5A factory / 10A field

current: 13.5A

voltage: 250V

wire section: 1.5mm²

torque: 0.5Nm

FILE: EQ202

MATERIALS

housing:	PA - UL 94 V0
screw:	Captive
clamp/spring:	Tin-plated copper alloy
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
--------------	------------	-----------------	----------------	----------------

2	MV152-5,08-V	N/A	N/A	N/A
3	MV153-5,08-V	N/A	N/A	N/A
4	MV154-5,08-V	N/A	N/A	N/A
5	MV155-5,08-V	N/A	N/A	N/A
6	MV156-5,08-V	N/A	N/A	N/A
7	MV157-5,08-V	N/A	N/A	N/A
8	MV158-5,08-V	N/A	N/A	N/A
9	MV159-5,08-V	N/A	N/A	N/A
10	MV1510-5,08-V	N/A	N/A	N/A
11	MV1511-5,08-V	N/A	N/A	N/A
12	MV1512-5,08-V	N/A	N/A	N/A
..	MV15..-5,08-V	N/A	N/A	N/A